



Date of issue 2021-02-20

Version 1.0

Total pages 39

Test report of

IES LM-79-08

Approved Method: Electrical and Photometric

Measurements of Solid-State Lighting Products

Applicant:

LIGHT EFFICIENT DESIGN

Address:

188 S. Northwest Highway Cary, IL 60013 USA

For Product:

4'T8 Lamps -- 4-Lamp External Driver (UL Type C) Lamps

Product Model No.:

RP-T8C-G2-30W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830,
RP-T8C-G2-30W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850,
RP-T8C-G2-35W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830,
RP-T8C-G2-35W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850,
RP-T8C-G2-40W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830,
RP-T8C-G2-40W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850,
RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830,
RP-T8C-G2-45W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850

Test laboratory: Shenzhen Belling Efficiency Testing Lab Co.,Ltd, 1Floor, No.1 Building, Meibaohe Industrial Park, Dalang Street, Longhua District, Shenzhen, Guangdong Prov.518101 China.

Complied by: Jarvis zhang

Review by: Jason zhou

Project Engineer

Technical Manager

Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or use in part without prior written consent from Shenzhen Belling Efficiency Testing Lab Co.,Ltd. This report must not be used by the customer to claim product certification, approval, or endorsement By NVLAP, NIST, or any agency of the U.S. Government.



1 General

1.1 Product Information

Manufacturer	LIGHT EFFICIENT DESIGN
Manufacturer Address	188 S. Northwest Highway Cary, IL 60013 USA
Brand Name	REMPHOS OR LIGHT EFFICIENT DESIGN
Luminaire Type	4'T8 Lamps -- 4-Lamp External Driver (UL Type C) Lamps
Test Model Number	RP-T8C-G2-30W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830, RP-T8C-G2-30W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850, RP-T8C-G2-35W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830, RP-T8C-G2-35W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850, RP-T8C-G2-40W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830, RP-T8C-G2-40W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850, RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830, RP-T8C-G2-45W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850
Rated Inputs	AC 100-277V 50/60Hz
Field-Adjustable Product	Yes, Wattage setting: 30W, 35W, 40W, 45W
Nominal CCT	3000K, 5000K
Dimming Capability	Continuous
Integral Control Sensors	Optional
Date of Receipt Samples	2020-12-21
Date of test	2020-12-23 to 2021-01-22
Burning Time Before Test	0hour(For New Products)

1.2 Standards or methods

- ANSI C78.377-2017:Specifications for the Chromaticity of Solid State Lighting Products
- ANSI C82.77-10:2014:Harmonic Emission Limits - Related Power Quality Requirements for Lighting Equipment - Solid State
- CIE Publication No.13.3-1995:Method of Measuring and Specifying Color Rendering of Light Sources
- IESNA LM-79-08 Approved Method: Electric & Photometric Measurement of Solid-state Lighting Products



1.3 Equipment list

Device	Manufacture	Model No.	Serial No.	Calibration due date
Goniophotometric System	SENSING	GMS-3000	N.A	2021-04-02
AC Power Source	ALL POWER	APW-110N	992257	2021-04-02
Total Luminous Flux Standard Lamp	SENSING	110V/100W	S1510065	2021-04-08
Total Spectral Radiant Flux Standard Lamp	SENSING	12V/20W	LSD12201731	2021-04-08
Digital Power Meter	YOKOGAWA	WT310	C2QM02030V	2021-04-02
Integral Sphere	SENSING	SPR-600M	N.A	2021-04-02
Digital Power Meter	YOKOGAWA	WT210	91L929742	2021-04-02
Optical Color and Electrical Measurement System	SENSING	SPR-3000	S1101108	2021-04-02
Environment Measurer	XUYAO	HS-1	N/A	2021-04-08
Environment Measurer	XUYAO	HS-1	N/A	2021-04-08
Stop watch	KISLO	K610	N/A	2021-04-27
Digital Anemometer	TECMAN	TD8901	026141	2021-09-09

Statement of Traceability: Shenzhen Belling Efficiency Testing Lab Co.,Ltd attests that all calibration has been performed using suitable standards traceable to national primary standards and International System of Unit (SI).



2 Test conducted and method

2.1 Ambient Condition

The ambient temperature in which measurements are being taken was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, the air flow around the sample(s) being tested did not affect the performance.

2.2 Power Supply Characteristics

The AC power supply had a sinusoidal voltage wave shape at the prescribed frequency (60 Hz) such that the RMS summation of the harmonic components does not exceed 3 percent of the fundamental during operation of the test item.

The voltage of AC power supply (RMS voltage) applied to the device under test was regulated to within ± 0.2 percent under load.

2.3 Seasoning and Stabilization

No seasoning was performed in accordance with IESNA LM-79-08. And before the measurement, the sample was stabilized until the light output and power variations were less than 0.5% in 30 minutes intervals (3 readings, 15 minutes apart).

2.4 Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, spectrophotometer, and integrating sphere. The integrating sphere system is calibrated by standard light source before measurement. The system and standard light source has been calibrated regularly and traceable to the National Primary Standards. 4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

Integrating Sphere Uncertainty: The uncertainty of the light output (luminous flux) measurements is $U=1.8\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=20\text{K}$ ($K=2$), at the 95% confidence level. The uncertainty of the CRI is $U=1.8(K=2)$, at the 95% confidence level. The uncertainty of power meter AC current $U=0.18\%$ of rdg, AC Voltage $U=0.16\%$ of rdg, Power $U=0.20\%$ ($K=2$), at the 95% confidence level.



2.5 Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement. The standard light source has been calibrated regularly and traceable to the National Primary Standards.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The method according to IESNA LM-79-08 following chapter.

Goniophotometer Uncertainty :The uncertainty of the luminous intensity is $U=1.6\%$ ($K=2$), at the 95% confidence level.



3 Test Result Summary

3.1 Integrating Sphere System (Total operating time for integrating sphere test: 1.0 hour)

3.1.1 Model Number: RP-T8C-G2-30W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830(Bare lamp)

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.19	60	0.064	7.67	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1085.80	141.56	2987


Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00035	0.4374	0.4034	0.2512	0.5212

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
83.2	11	84	94	-11

Spectral Distribution





7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-30W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4374
 y 0.4033
 u' 0.2512
 v' 0.5212

CIE 13.3-1995
(CRI)

R_a 83
 R_g 11

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.1.2 Model Number: RP-T8C-G2-30W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850(Bare lamp)

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.21	60	0.064	7.66	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1104.57	144.11	4998


Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00224	0.3456	0.3565	0.2099	0.4871

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
84.0	14	83	93	-12

Spectral Distribution





7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-30W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3456
 y 0.3565
 u' 0.2099
 v' 0.4871

CIE 13.3-1995
(CRI)

R_a 84
 R_g 14

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.1.3 Model Number: RP-T8C-G2-35W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830(Bare lamp)

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.18	60	0.073	8.78	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1224.66	139.48	2986


Chromaticity Coordinate

Duv	x	y	u'	v'
-0.0003	0.4375	0.4035	0.2512	0.5213

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
83.2	11	85	95	-11

Spectral Distribution





7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-35W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4375
 y 0.4035
 u' 0.2512
 v' 0.5213

CIE 13.3-1995
(CRI)

R_a 83
 R_g 11

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.1.4 Model Number: RP-T8C-G2-35W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850(Bare lamp)

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.20	60	0.073	8.77	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1242.98	141.77	4988


Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00226	0.3459	0.3568	0.2100	0.4873

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
84.0	14	83	93	-12

Spectral Distribution





7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-35W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

 x 0.3459 y 0.3568 u' 0.2100 v' 0.4873CIE 13.3-1995
(CRI) R_a 84 R_g 14

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.1.5 Model Number: RP-T8C-G2-40W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830(Bare lamp)

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.15	60	0.082	9.83	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1350.47	137.38	2990


Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00026	0.4373	0.4036	0.2510	0.5212

Color Rendering


CRI	R9	Rf	Rg	Rcs,h1(%)
83.1	11	84	95	-11

Spectral Distribution





7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-40W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4373
 y 0.4035
 u' 0.2510
 v' 0.5212

CIE 13.3-1995
(CRI)

R_a 83
 R_g 10

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.6 Model Number: RP-T8C-G2-40W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850(Bare lamp)****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.16	60	0.082	9.83	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1374.06	139.78	4996

Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00224	0.3457	0.3565	0.2099	0.4871


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
83.9	14	83	93	-12

Spectral Distribution



7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-40W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3457
 y 0.3565
 u' 0.2099
 v' 0.4871

CIE 13.3-1995
(CRI)

R_a 84
 R_g 14

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.7 Model Number: RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830(Bare lamp)****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.14	60	0.090	10.74	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1447.94	134.82	2990

Chromaticity Coordinate

Duv	x	y	u'	v'
-0.00015	0.4375	0.4039	0.2510	0.5214


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
83.0	10	84	95	-11

Spectral Distribution



7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4374
 y 0.4039
 u' 0.2510
 v' 0.5214

CIE 13.3-1995
(CRI)

R_a 83
 R_g 10

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.

**3.1.8 Model Number: RP-T8C-G2-45W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850(Bare lamp)****Electrical data**

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.14	60	0.089	10.70	0.996

Photometric data


Luminous Flux (lm)	Efficacy (lm/W)	CCT (K)
1475.50	137.86	4981

Chromaticity Coordinate

Duv	x	y	u'	v'
+0.00239	0.3461	0.3572	0.2099	0.4875


Color Rendering

CRI	R9	Rf	Rg	Rcs,h1(%)
83.8	13	83	93	-12

Spectral Distribution



7/4 Step Quadrangle











ANSI/IES TM-30-18 Color Rendition Report

Source: BL210126015-9

Manufacturer: LIGHT EFFICIENT DESIGN

Date: 2020/1/27

Model: RP-T8C-G2-45W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3461
 y 0.3572
 u' 0.2099
 v' 0.4875

CIE 13, 3-1995
(CRI)

R_a 84
 R_g 13

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.00.



3.2 Goniophotometer System (Total operating time for luminous intensity distribution: 1.0 hour)

3.2.1 Model Number: RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830(Bare lamp)

Electrical data

Input Voltage(V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
119.990	60	0.090	10.733	0.996

Photometric data

Luminous Flux (lm)	Efficacy (lm/W)	Beam Angle(°)
1449.27	135.03	183.9

**Zonal Flux Diagram**


Zonal flux distribution table

$\gamma(^{\circ})$	Average I(cd)	Zonal F(lm)	Sum F(lm)	Eff Flux(%)	Eff Sum(%)
0.0	277.612	0.000	0	0.00%	0.00%
5.0	278.000	6.642	6.642	0.00%	0.46%
10.0	274.999	19.783	26.425	0.00%	1.82%
15.0	269.591	32.305	58.729	0.00%	4.05%
20.0	262.241	43.830	102.56	0.00%	7.08%
25.0	253.185	54.059	156.619	0.00%	10.81%
30.0	242.853	62.774	219.392	0.00%	15.14%
35.0	230.813	69.751	289.143	0.00%	19.95%
40.0	217.930	74.869	364.012	0.00%	25.12%
45.0	203.842	78.094	442.107	0.00%	30.51%
50.0	189.341	79.448	521.555	0.00%	35.99%
55.0	174.947	79.208	600.763	0.00%	41.45%
60.0	160.716	77.588	678.351	0.00%	46.81%
65.0	146.898	74.781	753.132	0.00%	51.97%
70.0	133.403	70.974	824.106	0.00%	56.86%
75.0	120.735	66.427	890.534	0.00%	61.45%
80.0	109.181	61.519	952.053	0.00%	65.69%
85.0	99.100	56.595	1008.647	0.00%	69.60%
90.0	90.852	52.010	1060.658	0.00%	73.19%
95.0	84.150	47.917	1108.574	0.00%	76.49%
100.0	78.669	44.242	1152.816	0.00%	79.54%
105.0	73.637	40.753	1193.569	0.00%	82.36%
110.0	69.433	37.396	1230.965	0.00%	84.94%
115.0	64.599	33.938	1264.903	0.00%	87.28%
120.0	58.813	30.002	1294.904	0.00%	89.35%
125.0	53.943	26.063	1320.968	0.00%	91.15%
130.0	51.931	23.021	1343.988	0.00%	92.74%
135.0	49.936	20.584	1364.572	0.00%	94.16%
140.0	48.247	18.179	1382.751	0.00%	95.41%
145.0	47.097	15.907	1398.659	0.00%	96.51%
150.0	46.019	13.712	1412.371	0.00%	97.45%
155.0	44.941	11.511	1423.882	0.00%	98.25%
160.0	43.755	9.303	1433.184	0.00%	98.89%
165.0	42.641	7.120	1440.305	0.00%	99.38%
170.0	41.383	4.984	1445.289	0.00%	99.73%
175.0	41.850	2.978	1448.266	0.00%	99.93%
180.0	41.688	0.999	1449.265	0.00%	100.00%




Luminous Intensity Distribution Diagram

Light Distribution Curve [Unit:cd]





Lux distance Curve



Max , Ave

Beam angle of C90 plane 105.36

**Luminous Intensity Distribution Data**

C/ γ (°)	0.0	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0
0.0	277.61	258.18	255.88	251.86	248.41	244.96	240.07	235.18	229.72
22.5	277.61	265.08	261.06	257.03	252.72	246.39	239.49	231.73	223.68
45.0	277.61	274.28	271.69	266.81	259.91	251.28	241.79	230.58	217.93
67.5	277.61	272.27	268.24	261.34	252.43	240.64	227.13	211.03	194.35
90.0	277.61	303.61	300.44	294.12	284.92	272.27	257.61	239.78	220.23
112.5	277.61	298.72	295.56	290.09	280.89	269.11	255.59	239.49	221.96
135.0	277.61	290.67	288.37	284.34	277.73	269.68	259.33	247.54	234.61
157.5	277.61	270.26	268.53	265.37	261.63	256.46	248.41	241.51	232.88
180.0	277.61	257.32	258.76	255.31	250.99	246.11	241.22	234.03	227.71
202.5	277.61	262.49	262.78	260.77	255.59	250.71	244.96	236.62	227.42
225.0	277.61	273.71	270.83	264.79	257.03	247.26	237.48	225.69	213.90
247.5	277.61	271.69	267.67	260.48	250.71	238.63	225.41	209.59	192.92
270.0	277.61	299.01	291.82	281.47	267.96	252.43	234.32	213.62	192.34
292.5	277.61	294.41	288.37	278.59	266.81	251.86	236.04	219.08	200.39
315.0	277.61	287.79	283.19	276.58	268.82	259.62	249.27	237.77	225.41
337.5	277.61	268.53	266.81	264.51	259.33	253.58	247.54	239.78	231.44
360.0	277.61	258.18	255.88	251.86	248.41	244.96	240.07	235.18	229.72
C/ γ (°)	45.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0
0.0	217.93	208.73	202.40	194.93	186.02	177.10	169.63	160.72	151.80
22.5	213.04	202.40	193.78	185.15	175.67	167.62	158.99	151.52	143.18
45.0	205.85	192.05	177.39	163.30	151.52	140.02	129.38	119.89	111.55
67.5	177.10	159.57	141.45	124.49	107.53	90.85	75.04	62.39	53.76
90.0	199.24	176.82	154.39	130.53	106.67	84.24	59.80	38.24	18.69
112.5	203.27	184.58	164.17	145.19	127.37	108.68	91.71	76.48	64.11
135.0	220.81	206.72	191.77	178.25	164.74	152.09	140.59	128.80	117.88
157.5	224.26	214.48	204.42	193.78	184.58	174.52	164.74	154.97	145.19
180.0	219.66	211.03	203.84	194.35	185.44	176.82	167.62	158.70	149.50
202.5	219.08	210.45	200.39	191.19	179.98	170.49	160.72	152.09	141.74
225.0	201.25	188.89	175.95	163.59	150.65	139.15	128.52	117.88	108.39
247.5	176.24	158.70	140.30	121.62	105.52	89.99	76.76	64.69	54.63
270.0	170.20	146.34	123.05	99.48	77.05	54.05	32.20	13.80	3.16
292.5	181.70	162.73	143.47	125.35	108.97	91.43	77.05	65.26	57.21
315.0	210.45	196.94	182.28	168.19	155.25	143.75	133.12	124.78	117.30
337.5	221.38	209.02	200.10	192.05	183.43	173.65	165.89	156.69	147.49
360.0	217.93	208.73	202.40	194.93	186.02	177.10	169.63	160.72	151.80
C/ γ (°)	90.0	95.0	100.0	105.0	110.0	115.0	120.0	125.0	130.0
0.0	143.47	135.13	126.50	118.45	111.55	103.22	90.56	80.79	76.19
22.5	135.70	127.08	118.45	110.12	102.93	94.59	80.50	74.18	70.15
45.0	104.65	96.31	88.84	83.09	76.48	71.88	64.11	58.65	55.20
67.5	47.73	42.26	39.68	37.09	36.51	34.79	33.06	30.76	33.93
90.0	4.89	1.44	2.59	4.31	6.90	9.49	12.08	14.38	16.68
112.5	54.05	47.15	42.26	39.10	36.80	35.94	35.36	35.65	34.50
135.0	108.10	99.77	92.58	85.68	79.64	74.18	68.43	61.24	54.91
157.5	136.28	127.37	118.74	110.98	103.22	96.31	88.55	75.33	69.58
180.0	140.59	132.83	124.20	116.44	108.39	100.34	92.86	81.36	74.18
202.5	133.12	124.78	117.30	109.83	102.07	94.88	87.11	73.89	70.73
225.0	100.34	93.44	86.83	80.79	75.90	68.43	58.36	56.06	54.91
247.5	47.15	41.40	38.24	35.94	35.08	35.08	35.08	31.63	31.91
270.0	2.59	3.74	6.04	7.48	11.21	13.23	15.81	18.11	20.70
292.5	50.03	45.43	42.84	41.11	40.54	39.68	35.08	34.21	37.09
315.0	107.24	99.48	93.15	85.10	79.35	64.40	62.39	60.09	57.21
337.5	137.72	128.80	120.47	112.70	104.37	97.18	81.65	76.76	73.03
360.0	143.47	135.13	126.50	118.45	111.55	103.22	90.56	80.79	76.19



C/γ(°)	135.0	140.0	145.0	150.0	155.0	160.0	165.0	170.0	175.0
0.0	70.73	65.26	58.36	54.05	52.90	49.16	46.86	46.58	31.63
22.5	65.84	59.80	52.61	51.18	50.03	44.28	36.80	27.89	37.95
45.0	49.45	44.85	48.30	46.86	40.83	34.50	31.34	36.23	44.85
67.5	33.93	35.94	37.66	35.08	32.49	33.93	35.36	39.68	46.00
90.0	18.69	21.28	23.29	24.44	25.88	27.60	32.78	36.80	44.56
112.5	33.35	35.65	37.66	37.95	35.36	33.93	35.94	38.24	42.84
135.0	52.90	50.03	47.73	47.15	44.56	39.10	35.08	32.78	38.53
157.5	66.13	62.10	58.65	53.76	50.31	48.01	42.84	33.93	25.88
180.0	69.58	65.84	61.24	57.21	52.90	50.03	47.73	46.29	46.00
202.5	67.28	63.54	61.24	58.36	55.49	53.19	50.89	48.30	47.44
225.0	52.61	50.89	48.59	48.30	49.16	50.31	50.89	50.31	43.13
247.5	33.06	34.79	36.80	39.39	42.84	45.71	48.59	42.84	41.40
270.0	23.00	24.73	26.16	27.03	28.75	34.79	37.95	44.28	51.75
292.5	39.10	40.54	42.26	44.28	47.73	49.74	45.14	43.99	47.44
315.0	54.34	51.18	52.04	53.19	52.90	52.61	52.90	44.85	43.99
337.5	69.00	65.55	60.95	58.08	56.93	53.19	51.18	49.16	36.23
360.0	70.73	65.26	58.36	54.05	52.90	49.16	46.86	46.58	31.63
C/γ(°)	180.0								
0.0	41.69								
22.5	41.69								
45.0	41.69								
67.5	41.69								
90.0	41.69								
112.5	41.69								
135.0	41.69								
157.5	41.69								
180.0	41.69								
202.5	41.69								
225.0	41.69								
247.5	41.69								
270.0	41.69								
292.5	41.69								
315.0	41.69								
337.5	41.69								
360.0	41.69								



4 Additional Test

Electrical data at 277V

Model Number	Test Item	Test Voltage (V)	Frequency (Hz)	Test Result
RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830	Power Factor	277	60	0.969
	THD	277	60	6.0%

5 Performance Assessment

Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T8C-G2-30W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830	3000	1085.80	7.67	141.56
RP-T8C-G2-30W-4FT-4L-835-[OCN, Blank]-10V/RP-T8C-G2-4FT-835	3500	1090.49 ^{*1}	7.67 ^{*2}	142.27 ^{*3}
RP-T8C-G2-30W-4FT-4L-840-[OCN, Blank]-10V/RP-T8C-G2-4FT-840	4000	1095.19 ^{*1}	7.67 ^{*2}	142.88 ^{*3}
RP-T8C-G2-30W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850	5000	1104.57	7.66	144.11

*1: This value is calculated and the calculation formula is as below:

$$1090.49 = (1104.57 - 1085.80) / 4 + 1085.80$$

$$1095.19 = (1104.57 - 1085.80) / 4 + 1090.49$$

*2: This value is calculated and the calculation formula is as below:

$$7.67 = (7.67 + 7.66) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$142.27 = 1090.49 / 7.67$$

$$142.88 = 1095.19 / 7.67$$



Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T8C-G2-35W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830	3000	1224.66	8.78	139.48
RP-T8C-G2-35W-4FT-4L-835-[OCN, Blank]-10V/RP-T8C-G2-4FT-835	3500	1229.24 ^{*1}	8.78 ^{*2}	140.08 ^{*3}
RP-T8C-G2-35W-4FT-4L-840-[OCN, Blank]-10V/RP-T8C-G2-4FT-840	4000	1233.82 ^{*1}	8.78 ^{*2}	140.61 ^{*3}
RP-T8C-G2-35W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850	5000	1242.98	8.77	141.77

*1: This value is calculated and the calculation formula is as below:

$$1229.24 = (1242.98 - 1224.66) / 4 + 1224.66$$

$$1233.82 = (1242.98 - 1224.66) / 4 + 1229.24$$

*2: This value is calculated and the calculation formula is as below:

$$8.78 = (8.78 + 8.77) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$140.08 = 1229.24 / 8.78$$

$$140.61 = 1233.82 / 8.78$$

Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T8C-G2-40W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830	3000	1350.47	9.83	137.38
RP-T8C-G2-40W-4FT-4L-835-[OCN, Blank]-10V/RP-T8C-G2-4FT-835	3500	1356.37 ^{*1}	9.83 ^{*2}	137.98 ^{*3}
RP-T8C-G2-40W-4FT-4L-840-[OCN, Blank]-10V/RP-T8C-G2-4FT-840	4000	1362.27 ^{*1}	9.83 ^{*2}	138.58 ^{*3}
RP-T8C-G2-40W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850	5000	1374.06	9.83	139.78

*1: This value is calculated and the calculation formula is as below:

$$1356.37 = (1374.06 - 1350.47) / 4 + 1350.47$$

$$1362.27 = (1374.06 - 1350.47) / 4 + 1356.37$$

*2: This value is calculated and the calculation formula is as below:

$$9.83 = (9.83 + 9.83) / 2$$

*3: This value is calculated and the calculation formula is as below:

$$137.98 = 1356.37 / 9.83$$

$$138.58 = 1362.27 / 9.83$$



Model name	CCT(K)	Total Luminous(lm)	Power(W)	Luminous Efficacy(lm/W)
RP-T8C-G2-45W-4FT-4L-830-[OCN, Blank]-10V/RP-T8C-G2-4FT-830	3000	1447.94	10.74	134.82
RP-T8C-G2-45W-4FT-4L-835-[OCN, Blank]-10V/RP-T8C-G2-4FT-835	3500	1454.83 ^{*1}	10.72 ^{*2}	135.71 ^{*3}
RP-T8C-G2-45W-4FT-4L-840-[OCN, Blank]-10V/RP-T8C-G2-4FT-840	4000	1461.72 ^{*1}	10.72 ^{*2}	136.35 ^{*3}
RP-T8C-G2-45W-4FT-4L-850-[OCN, Blank]-10V/RP-T8C-G2-4FT-850	5000	1475.50	10.70	137.86

*1: This value is calculated and the calculation formula is as below:

$$1454.83 = (1475.50 - 1447.94) / 4 + 1447.94$$

$$1461.72 = (1475.50 - 1447.94) / 4 + 1454.83$$

*2: This value is calculated and the calculation formula is as below:

$$10.72 = (10.74 + 10.70) / 2$$


*3: This value is calculated and the calculation formula is as below:

$$135.71 = 1454.83 / 10.72$$

$$136.35 = 1461.72 / 10.72$$



Photo Document



****End of test report****